

Product Information

AVENO Semi Synth. 10W-30

0002-000027



Description

AVENO Semi Synth. 10W-30 is a semi-synthetic high-performance, smooth-running engine oil for gasoline car engines with or without turbocharging and direct injection. Extended oil change intervals as per manufacturer's instructions. AVENO Semi Synth. 10W-30 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. With AVENO Semi Synth. 10W-30, a reliable and heavy-duty engine oil has been developed.

Instructions for use

AVENO Semi Synth. 10W-30 is an engine oil for year-round use, and is ideal for all modern petrol car engines. AVENO Semi Synth. 10W-30 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SN/SM
- ILSAC GF-5

Recommendation

- Chrysler MS-6395
- Daewoo
- Daihatsu
- Fiat 9.55535-CR1
- GM 6094M
- Honda
- Hyundai
- Isuzu
- KIA
- Mazda
- Mitsubishi
- Nissan
- SsangYong
- Subaru
- Suzuki
- Toyota

Properties

- Excellent cold starting properties, even at low temperatures
- A very stable viscosity behavior and shear stability
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Reduction of fuel consumption under all operating conditions
- Low evaporation, thus low oil consumption
- Extensive protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	63,9	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	10,1	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	144		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -25°C	4800	mpa*s	ASTM D 5293:2020
Density at 15°C	861	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015
Total Base Number (TBN)	7,8	mgkoh/g	ASTM D 2896:2015