



Product certificate

AVENO Super Truck 10W

0002-000089

Description

AVENO Super Truck 10W is a high-alloyed HD engine oil for use in diesel lorry engines with and without turbo charging, as well as for stationary systems.

AVENO Super Truck 10W offers a balanced additive package and guarantees high wear and corrosion protection.

Instructions for use

AVENO Super Truck 10W is used in diesel lorry engines with and without turbo charging, as well as in stationary systems. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- ACEA E2/B4
- API CF-4/SG
- MIL-L-2104 D
- MIL-L-46152 B

AVENO Super Truck 10W is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- Allison C-4
- Caterpillar TO-2
- MAN 270
- MB 228.0, MB 235.27
- Voith Retarder A
- ZF TE-ML 03B/03C/04B/05K

Properties

- A very stable and excellent viscosity and temperature behavior
- High oxidation stability
- Good shear stability
- Good lubrication properties, even at high oil temperatures
- Ideal for difficult operating conditions
- Prevention of wear
- Compelling detergent/dispersant properties
- Neutrality towards sealants
- Good cold starting properties
- Prevents black sludge

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	42,9	MM ² /S	DIN ISO 51562-2:1988-12
kinematic viscosity at 100°C	7	MM ² /S	DIN ISO 51562-2:1988-12
viscosity index	123		DIN ISO 2909:2004-08
appearance	YELLOWBROWN		VISUELL
density at 15°C	864	KG/M ³	DIN EN ISO 12185:1997-11
Pour Point	-42	°C	ASTM D 7346:2015

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.