



Product certificate

AVENO MotorCycle 4 Stroke Mineral 15W-40

0002-000124

Description

AVENO MotorCycle 4 Stroke Mineral 15W-40 is a mineral-based engine oil with selected additives for demanding 4-stroke motorbikes. It is characterised by its high durability and reliability and is specifically designed for wet and lubricated couplings.

AVENO MotorCycle 4 Stroke Mineral 15W-40 has an outstanding lubrication film adhesion and good shear stability as well as excellent cleaning properties and high resistance to ageing.

Instructions for use

AVENO MotorCycle 4 Stroke Mineral 15W-40 is a suitable engine oil for all motorcycles, when the specification SAE 15W-40 is required. For professional racing we recommend our racing products.

Quality classification

Specification

- API SL
- JASO MA-2

AVENO MotorCycle 4 Stroke Mineral 15W-40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

Properties

- Excellent cold starting properties
- High oxidation stability
- Excellent shear stability
- Very good detergent and dispersing properties
- Very good viscosity-temperature behaviour
- Suitable for catalytic converters
- Prevents black sludge from forming
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	105,5	MM ² /S	DIN ISO 51562-2:1988-12
kinematic viscosity at 100°C	14,2	MM ² /S	DIN ISO 51562-2:1988-12
viscosity index	136		DIN ISO 2909:2004-08
appearance	YELLOWBROWN		VISUELL
density at 15°C	872	KG/M ³	DIN EN ISO 12185:1997-11
Pour Point	-36	°C	ASTM D 7346:2015

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.