



Product certificate

AVENO Circulating Oil CL 680

0002-000273

Description

A mild additive and is therefore particularly suitable for old machines

A good wear protection

Inhibits rust and corrosion and protects against ferrous metal corrosion

Prevents foam formation

Good water separation characteristics

AVENO CL Circulating Oil 680 is produced on a basis of high-quality mineral oils and proven additives. Thanks to its special combination of active ingredients, it is suitable for use as a simple machine lubricant where no EP-additive oils are required.

Instructions for use

AVENO CL Circulating Oil 680 has very good properties as a lubricant. Therefore AVENO CL Circulating Oil 680 can preferably be used for industrial gears and circulation systems of low and medium loads, where lubricants are required in accordance with DIN 51517-2.

Quality classification

Specification

- DIN 51517-2 CL

AVENO Circulating Oil CL 680 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

Properties

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	685,400	MM ² /S	DIN ISO 51562-2:1988-12
viscosity index	111		DIN ISO 2909:2004-08
appearance	YELLOW		VISUELL
density at 15°C	908	KG/M ³	DIN EN ISO 12185:1997-11
Pour Point	-9	°C	ASTM D 7346:2015

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

22.03.2021 10:52:50