



## Product certificate

**AVENO Super Truck 60**

**0002-000535**

### Description

AVENO Super Truck 60 is an HD engine oil, high-alloyed with synthetic additives suitable for diesel lorry engines, including with turbo charging. With AVENO Super Truck 60 a reliable and heavy-duty engine oil has been developed.

### Instructions for use

AVENO Super Truck Turbo 60 is an engine oil for year-round use, and is suitable for diesel engines and commercial vehicle engines with and without turbo charging.

AVENO Super Truck Turbo 60 can be used in engines with the specifications indicated. The operating instructions of the engine manufacturer must be observed.

### Quality classification

#### Specification

- API CF-4/SG
- MIL-L-2104 D
- ACEA E2/B4

**AVENO Super Truck 60 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:**

- Allison C-4
- Caterpillar TO-2
- Deutz DQC I-02
- MB 228.0
- ZF TE-ML 04B/04E

### Properties

- A stable and excellent viscosity behavior
- Good detergent and dispersing properties
- Neutrality towards sealants
- Extensive protection against wear, corrosion and foaming
- Suitable for catalytic converters
- A very good shear stability
- Prevention of black sludge formation
- High safety margin even in boundary lubrication
- A high oxidation stability

### Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	306,4	MM <sup>2</sup> /S	DIN ISO 51562-2:1988-12
kinematic viscosity at 100°C	24,2	MM <sup>2</sup> /S	DIN ISO 51562-2:1988-12
Viscosity Index	101		DIN ISO 2909:2004-08
appearance	YELLOWBROWN		VISUELL
density at 15°C	898	KG/M <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-12	°C	ASTM D 7346:2015

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.