

Product Information

AVENO Mineral Turbo 10W-40

0002-000012



Description

AVENO Mineral Turbo 10W-40 is a mineral engine oil for gasoline and diesel engines with and without turbocharging. AVENO Mineral Turbo 10W-40 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear. With AVENO Mineral Turbo 10W-40 a reliable and heavy-duty engine oil was developed.

Instructions for use

Mineral Turbo 10W-40 is an engine oil for year-round use, and is ideal for all modern petrol and diesel car engines. Mineral Turbo 10W-40 can be used in engines with the specifications indicated. The operating instructions of the car and engine manufacturers must be observed.

Quality classification

Specification

- API CH-4
- API SL/CF
- ACEA A3/B4
- ACEA E2

Recommendation

- Cummins CES 20071
- Deutz DQC II-10
- Mack EO-M
- MAN 271
- MB 228.1, MB 229.1
- MTU Type 1
- VOLVO VDS
- VW 501 01/VW 505 00

Properties

- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Suitable for catalytic converters
- Excellent cold starting properties, even at low temperatures below -25°
- A very stable and excellent viscosity behavior and shear stability
- Extensive protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	95.5	mm ² /s	DIN ISO 51562-2:1988-12
Kinematic Viscosity at 100°C	14.4	mm ² /s	DIN ISO 51562-2:1988-12
Viscosity Index	156		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	862	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015