

Product Information

AVENO Semi Synth. 20W-50

0002-000024



Description

AVENO Semi Synth. 20W-50 is a partially synthetic multigrade engine oil for petrol and diesel car engines with or without turbocharging and commercial vehicle engines. It facilitates extended oil change intervals as per the manufacturer's instructions. AVENO Semi Synth. 20W-50 is characterised by its good cold starting properties, minimisation of fuel consumption, friction and wear. With AVENO Semi Synth. 20W-50 a reliable and heavy-duty engine oil has been developed.

Instructions for use

AVENO Semi Synth. 20W-50 is an engine oil for year-round use and is suitable for petrol and diesel car engines and commercial vehicle engines. AVENO Semi Synth. 20W-50 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturers must be observed.

Quality classification

Specification

- ACEA A3/B4, E2
- API SL/CF

Recommendation

- MAN 271
- MB 228.1, 229.1
- VW 505 00
- MTU
- Volvo VDS

Properties

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	18,85	mm ² /s	DIN ISO 51562-2:1988-12
viscosity index	129		DIN ISO 2909:2004-08
appearance	YELLOWBROWN		VISUELL
density at 15°C	883	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-30	°C	ASTM D 7346:2015