

Product Information

AVENO Maxi Fuel Economy 0W-16 GREEN

0002-000053



Description

AVENO Maxi Fuel Economy 0W-16 GREEN is a fully synthetic low-friction engine oil for passenger car gasoline and diesel engines with and without turbocharging and direct injection. AVENO Maxi Fuel Economy 0W-16 GREEN is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear. Extended oil change intervals according to the manufacturer's instructions.

Instructions for use

AVENO Maxi Fuel Economy 0W-16 GREEN is ideally suited for energy-saving year-round use in all modern passenger car gasoline and diesel engines. It thus reduces CO² emissions and helps protect the environment. AVENO Maxi Fuel Economy 0W-16 GREEN is used in engines with the specified specifications. The operating regulations of the vehicle and engine manufacturers must be observed.

Quality classification
Specification

- API SP
- ILSAC GF-5/GF-6B

Recommendation

- Honda 08215-99974, Honda 08216-99974
 - Honda 08232-P99S1LHE, Honda Ultra Next/Ultra Green
 - Hybrid Engine Nissan KLANM-01A04 Extra Save X Eco
- Mitsubishi Diaqueen ECO Plus
 - Mitsubishi MZ102661, Mitsubishi MZ102662
 - Toyota 08880-11005

Properties

- Fuel savings under all operating conditions
 - Very good detergent and dispersing properties
 - Neutrality towards sealing materials
 - Catalyst suitability
 - Extended oil change intervals protect natural resources
- Excellent cold start properties even at low temperatures
 - An extremely stable and excellent viscosity behavior, shear stability
 - Low evaporation tendency, therefore low oil consumption
 - Excellent protection against wear, corrosion and foam formation

Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	39.1	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	7.3	mm²/s	DIN 51659-2:2017-02
Viscosity Index	154		DIN ISO 2909:2004-08
Appearance	GREEN		VISUELL
Viscosity CCS at -35°C	4410	mPa*s	ASTM D 5293:2020
Density at 15°C	842	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-66	°C	ASTM D 7346:2015
Total Base Number (TBN)	8.1	mgKOH/g	ASTM D 2896:2015