Product Information AVENO STOU 15W-40

0002-000117



Description

AVENO STOU 15W-40 is a modern multi-purpose oil for agricultural machines, excavators and construction equipment. AVENO STOU 15W-40 is manufactured from high-quality base oils and selected additives and can be used equally in engines, gearboxes and hydraulic systems of modern agricultural machinery.

Instructions for use

Quality classification

AVENO STOU 15W-40 is suitable for year-round use as an engine oil for petrol engines and aspirated and turbocharged diesel engines, as a gear oil (including wet brakes) and as a hydraulic oil in tractors and agricultural machinery.

| Specification | | |
|---------------------|--|--|
| • API GL-4 | • ACEA E2 | |
| • API SF/CF/CG-4 | • MIL-L-2104 D | |
| Recommendation | | |
| • Allison C-4 | • MAN 271 | |
| Caterpillar TO-2 | Massey Ferguson CMS 1139/1144/1145 | |
| • Ford ESN-M2C159-B | • MB 227.1, MB 228.1, DTFR 15B110 (228.3) | |
| • John Deere J 27 | • ZF TE-ML 06A/06B/06C/06D/07B | |
| | | |

Properties

- A high dispersion and detergent capability
- High oxidation stability
- A high and stable viscosity index

- Outstanding high-pressure properties
- Protection against wear, corrosion and foaming

| Technical specifications | | | |
|------------------------------|-------|---------|--------------------------|
| Properties | Data | Unit | Testing under |
| Kinematic Viscosity at 40°C | 83.6 | mm²/s | DIN 51659-2:2017-02 |
| Kinematic Viscosity at 100°C | 13.1 | mm²/s | DIN 51659-2:2017-02 |
| Viscosity Index | 157 | | DIN ISO 2909:2004-08 |
| Appearance | BROWN | | VISUELL |
| Viscosity CCS at -20°C | 2510 | MPAS | ASTM D 5293:2020 |
| Density at 15°C | 868 | kg/m³ | DIN EN ISO 12185:1997-11 |
| Pour Point | -39 | °C | ASTM D 7346:2015 |
| Total Base Number (TBN) | 12.8 | mgKOH/g | ASTM D 2896:2015 |