

Product Information

AVENO TO-4 SAE 50

0002-000120



Description

AVENO TO-4 SAE 50 is a special transmission oil for supplying construction machinery and tractors. AVENO TO-4 SAE 50 meets the increased demands of the Caterpillar TO-4 specification and is therefore suitable for use in gearboxes, final drives, hydraulic systems, wet brakes and clutches which require this specification.

Instructions for use

AVENO TO-4 SAE 50 ensures maximum wear protection in various gearboxes, such as side drives and differentials, it optimizes the friction coefficient in power-shift transmissions, wet brakes and clutches and guarantees maximum service life for the units.

Quality classification

Specification

- API CF
- API MT-1

Recommendation

- Allison C-4
- Caterpillar TO-4M/FD-1
- Komatsu KES 07.868.1
- ZF TE-ML 03C

Properties

- A high dispersion and detergent capability
- High oxidation stability
- A high and stable viscosity index
- Outstanding high-pressure properties
- Protection against wear, corrosion and foaming

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	183,9	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	16,8	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	96		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	895	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-21	°C	ASTM D 7346:2015
Total Base Number (TBN)	9,3	mgkoh/g	ASTM D 2896:2015