

Product Information

AVENO MotorCycle 4 Stroke Mineral 15W-40

0002-000124



Description

AVENO MotorCycle 4 Stroke Mineral 15W-40 is a mineral-based engine oil with selected additives for demanding 4-stroke motorbikes. It is characterised by its high durability and reliability and is specifically designed for wet and lubricated couplings. AVENO MotorCycle 4 Stroke Mineral 15W-40 has an outstanding lubrication film adhesion and good shear stability as well as excellent cleaning properties and high resistance to ageing.

Instructions for use

AVENO MotorCycle 4 Stroke Mineral 15W-40 is a suitable engine oil for all motorcycles, when the specification SAE 15W-40 is required. For professional racing we recommend our racing products.

Quality classification

Specification

- API SL
- JASO MA-2

Properties

- Excellent cold starting properties
- Excellent shear stability
- Very good viscosity-temperature behaviour
- Prevents black sludge from forming
- High oxidation stability
- Very good detergent and dispersing properties
- Suitable for catalytic converters

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	105,5	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	14,2	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	136		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -20°C	6500	mpas	ASTM D 5293:2020
Density at 15°C	872	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-36	°C	ASTM D 7346:2015
Total Base Number (TBN)	8,1	mgkoh/g	ASTM D 2896:2015