

Product Information

AVENO MotorCycle 4 Stroke Mineral 20W-40

0002-000125



Description

AVENO MotorCycle 4 Stroke Mineral 20W-40 is a mineral based engine oil with selected additives for demanding 4-stroke motorbikes. It is characterized by its high durability and reliability and is specifically designed for wet and lubricated couplings. AVENO MotorCycle 4 Stroke Mineral 20W-40 has an outstanding lubrication film adhesion and good shear stability as well as excellent cleaning properties and high resistance to aging.

Instructions for use

AVENO MotorCycle 4 Stroke Mineral 20W-40 is a suitable engine oil for all motorcycles, when the specification SAE 20W-40 JASO MA/MA2 is required. For professional racing we recommend our racing products.

Quality classification

Specification

- API SM
- JASO MA/MA2

Properties

- Excellent cold starting properties
- Excellent shear stability
- Very good viscosity-temperature behavior
- High safety margin even in boundary lubrication
- High oxidation stability
- Very good detergent and dispersing properties
- Suitable for catalytic converters
- Prevents black sludge from forming

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	110,0	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	14,4	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	133		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -15°C	4000	mpa*s	ASTM D 5293:2020
Density at 15°C	873	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-36	°C	ASTM D 7346:2015
Total Base Number (TBN)	8,4	mgkoh/g	ASTM D 2896:2015