

Product Information

AVENO Selfmix 2-stroke engine RED

0002-000138



Description

AVENO Selfmix 2-stroke engine RED is a premixed, mineral oil-based lubricant for 2-stroke engines. It reduces carbon deposits in the piston ring grooves, the combustion evicton and the outlet ports. AVENO Selfmix 2-stroke engine RED reduces rust damage in the engine parts and the dirtying of spark plugs.

Instructions for use

AVENO Selfmix 2-stroke engine RED is recommended for the lubrication of air and water cooled 2-stroke petrol engines such as lawn mowers, motorcycles, mopeds, scooters, chain saws etc. AVENO Selfmix 2-stroke engine RED is suitable for the lubrication of separate lubricating systems or self-mixing systems. Recommended mixing ratio: 1:50 (oil : fuel) Observe manufacturer's instructions.

Quality classification

Specification

- API TC
- ISO-L-EGB
- JASO FB

Properties

- Excellent corrosion protection
- Excellent oxidation stability
- Very good wear protection
- Reduction of coking
- Environmentally friendly with low smoke emissions

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	66,6	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	9,0	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	110		DIN ISO 2909:2004-08
Appearance	RED		VISUELL
Density at 15°C	875	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-27	°C	ASTM D 7346:2015