# **Product Information**

## **AVENO FS 2-stroke engine COLORLESS**

### 0002-000143



### Description

AVENO FS 2-stroke engine COLORLESS is a synthetic 2-stroke oil based on synthetic base oils, selected 2-stroke additives and a PIB component. It is characterised by its high wear protection and reduced corrosion, as well as a prevention of deposits and glow-ignitions. AVENO FS 2-stroke engine COLORLESS is ideally suited to air and watercooled 2-stroke engines, as well as for separate-lubrication and self-mixing systems.

### Instructions for use

AVENO FS 2-stroke engine COLORLESS is recommended for the lubrication of air-cooled 2-stroke petrol engines with a very high speed and the heaviest loads, as well as for the lubrication of separate-lubrication and self-mixing systems. AVENO FS 2-stroke engine COLORLESS is suitable for high-quality, high speed units such as brush cutters, leaf vacuums, Chainsaw and so on, with over 6,000 rpm.

Quality classification		
Specification		
API TC JASO FD	• ISO-L-EGD	
Recommendation		
Husqvarna Piaggio Hexagon	• Rotax • Stihl	
Properties		

- High cleaning performance
- Possible extent
- Excellent lubrication of all engine parts
- High wear and corrosion protection

- Free of combustion residue and deposits to the greatest
- Clean spark plugs provide for an optimum performance of the engine
- Low exhaust fumes due to high combustion rate

Technical specifications				
Properties	Data	Unit	Testing under	
Kinematic Viscosity at 40°C	68.0	mm²/s	DIN 51659-2:2017-02	
Kinematic Viscosity at 100°C	10.6	mm²/s	DIN 51659-2:2017-02	
Viscosity Index	144		DIN ISO 2909:2004-08	
Appearance	YELLOWBROWN		VISUELL	
Density at 15°C	868	kg/m³	DIN EN ISO 12185:1997-11	
Pour Point	-39	°C	ASTM D 7346:2015	