

Product Information

AVENO Dexron D II RED

0002-000157



Description

AVENO Dexron D II RED is a very high-quality gear fluid for automatic gearboxes of all vehicles and machinery. It is made with a base of highly refined mineral oils with suitable additives. It was developed especially for the indicated specifications and purposes. AVENO Dexron D II RED provides maximum lubrication and wear protection thanks to its special additives.

Instructions for use

AVENO Dexron D II RED was developed for use in automatic gearboxes, hydraulic steering systems, converters and power transmissions, and can be used as a universal ATF (automatic transmission fluid) for all vehicles and machinery. It is recommended if an ATF type Dexron D II must be used in accordance with the manufacturer's specifications. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- GM Dexron® II D
- Ford MERCON®

Recommendation

- Caterpillar TO-2
- Ford ESP-M2C166-H, Ford WSS-M2C185-A
- Ford SQM-2C9010-B, Ford WSS-M2C138-CJ
- MAN 339 Typ Z1
- DTFR 13C120 (236.2), MB 236.6
- DTFR 13C140 (236.7)
- Renk Doromat
- VOITH 55.6335.xx
- ZF TE-ML 03D/04D/11A/14A/17C/05L

Properties

- Stable and excellent viscosity-temperature behavior
- Problem-free, both at very low and very high temperatures
- Extremely high thermal load bearing capacity
- Neutral towards sealing agents
- Reliable protection against wear, silting, bonding and corrosion
- Foam-free, even under the heaviest of loads
- Miscibility and compatibility with all brands of ATFs

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	35,0	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	7,2	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	176		DIN ISO 2909:2004-08
Appearance	RED		VISUELL
Density at 15°C	852	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-54	°C	ASTM D 7346:2015