

Product Information

AVENO MTF Universal 75W-80

0002-000159



Description

AVENO MTF Universal 75W-80 is a synthetic 75W-80 gear oil designed to provide enhanced EP performance compared with a conventional GL-4 fluid in combination with synchroniser compatibility and fuel efficiency benefits.

Instructions for use

AVENO MTF Universal 75W-80 is suitable for transaxles, manual gearboxes, transfer boxes and final drives where an API GL-4 lubricant is specified. It is not suitable for use where API GL-5 is requested. Recommended for all 5- and 6-speed manual transmissions of Volkswagen, Audi, Seat and Skoda.

Quality classification

Specification

- API GL-4

Recommendation

- Audi/VW G 009 317, Audi/VW G 052 171
- Audi/VW G 052 178, Audi/VW G 052 512
- Audi/VW G 052 527 A2, Audi/VW G 052 532
- Audi/VW G 052 726, Audi/VW G 052 798
- Audi/VW G 060 726, Audi/VW G 070 726 A2
- BMW MTF LT-2, BMW MTF LT-3, BMW MTF LT-4
- Fiat 9.55550-MZ2
- Ford WSS-M2C200-D2
- GM 194004, 19259104 (BOT 303), 1940764, 1940768
- Honda MTF 94
- Honda MTF, Honda MTF-II, Honda MTF-III
- MB 235.10
- Nissan MT-XZ, Nissan MT-XZ TL (JR Type)
- Opel 9163335
- PSA 9730 A2/A8
- PSA B71 2330
- Toyota JWS 227
- Tranself NFJ, Tranself NFP
- Tranself TRJ, Tranself TRT, Tranself TRZ
- VOLVO 97308, VOLVO 97309

Properties

- Very good thermal-oxidative stability
- Clean gears and longer oil life
- Very good synchronicity
- Good shear stability
- Very low switching forces even at low temperatures
- Fuel savings and low emissions
- Long lubrication security with constant functionality

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	51,8	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	8,8	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	149		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	865	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-48	°C	ASTM D 7346:2015