

# Product Information

## AVENO Gear Extra Full Synth. LS 75W-140 GL-5

0002-000222



### Description

AVENO Gear Extra Full Synth. LS 75W-140 GL-5 is a fullysynthetic multi-purpose oil for highly stressed manual gearboxes. AVENO Gear Extra Full Synth LS 75W-140 GL 5 was developed based on the high quality fully synthetic base oils (PAO and Ester) with a special additive treatment and inhibition for limited slip applications. AVENO Gear Extra Full Synth. LS 75W-140 GL-5 is coordinated to the increased loads of manual gearbox oils, in order to ensure the gearbox functions flawlessly.

### Instructions for use

AVENO Gear Extra Full Synth. LS 75W-140 GL-5 guarantees proper lubrication, even in self-locking, hypoid-geared gearboxes. The operating instructions of the automobile and gearbox manufacturer must be observed.

Quality classification			
Specification			
<ul style="list-style-type: none"><li>• API GL-4</li><li>• MIL-L-2105 C</li></ul>		<ul style="list-style-type: none"><li>• API GL-5</li><li>• MIL-L-2105 D</li></ul>	
Recommendation			
<ul style="list-style-type: none"><li>• BMW 83 22 2 282 583, BMW 83 22 1 470 080</li><li>• BMW MSP/A</li><li>• Castrol SAF-XJ</li></ul>		<ul style="list-style-type: none"><li>• Ford M2C187-A, Ford M2C192-A</li><li>• Ford M2C192-A + M2C118-A</li><li>• GM 12346140, GM 1942386</li></ul>	
Properties			
<ul style="list-style-type: none"><li>• Less wear</li><li>• Very good oxidation stability</li><li>• Resistant oil film</li></ul>		<ul style="list-style-type: none"><li>• Excellent viscosity-temperature characteristics</li><li>• Neutral towards metal and sealing agents</li></ul>	
Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	205.2	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	28.2	mm²/s	DIN 51659-2:2017-02
Viscosity Index	177		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	845	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-51	°C	ASTM D 7346:2015