Product Information

AVENO CLP 150

0002-000296



Description

AVENO CLP 150 is produced on a basis of high-quality mineral oils and proven additives. Thanks to its special combination of ingredients, it achieves a stable, highpressure capacity under impact loads. Due to the low pour point of AVENO CLP 150, the cold behavior of this product is excellent.

Instructions for use

AVENO CLP 150 has very good properties as a lubricant. AVENO CLP 150 can therefore be used in largely all industrial areas under stress and impact loads.

Quality classification				
Specification				
• AGMA 9005-D94		• DIN 51517-3	• DIN 51517-3	
Recommendation				
Cincinnati Milacron		• US Steel 224	• US Steel 224	
Clean Panel Coker		• US Steel S-200	• US Steel S-200	
Properties				
• An excellent cold behavior		 A stable, high-pressure 	• A stable, high-pressure capacity under impact loads	
An excellent wear protection		 A low pour point 	• A low pour point	
Prevents foam formation		 Inhibits rust and corrosi 	Inhibits rust and corrosion	
 Zinc free, ash free 				
Technical specifications				
Properties	Data	Unit	Testing under	
Kinematic Viscosity at 40°C	152.3	mm²/s	DIN 51659-2:2017-02	
Kinematic Viscosity at 100°C	14.8	mm²/s	DIN 51659-2:2017-02	
Viscosity Index	96		DIN ISO 2909:2004-08	
Appearance	YELLOW		VISUELL	
Density at 15°C	887	kg/m³	DIN EN ISO 12185:1997-11	
Pour Point	-27	°C	ASTM D 7346:2015	

Deutsche Ölwerke Lubmin GmbH | Freesendorfer Weg 4 | 17509 Lubmin | Phone +49 38354 / 179530 | Fax +49 38354 / 179579

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.