Product Information

AVENO CLP 680

0002-000302



Description

AVENO CLP 680 is produced on the basis of high quality mineral oils and proven additives. Its special combination of active ingredients achieves a stable highpressure absorption capacity under impact loads. Due to the low pour point of AVENO CLP 680, the cold behavior of this product is excellent.

Instructions for use

AVENO CLP 680 has very good properties as a lubricant. AVENO CLP 680 can therefore be used in largely all industrial areas under stress and impact loads.

Quality classification			
Specification			
• AGMA 9005-D94		• DIN 51517-3	
Recommendation			
• Cincinnati Milacron • Clean Panel Coker		• US Steel 224 • US Steel S-200	
Properties			
An excellent cold behaviorAn excellent wear protectionPrevents foam formation		 A low pour point Inhibits rust and corrosion Zinc free 	
Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	676.0	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	39.0	mm²/s	DIN 51659-2:2017-02
Viscosity Index	96		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	902	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-15	°C	ASTM D 7346:2015

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.