

Product Information

AVENO Break-In Oil SAE 30 RED

0002-000304



Description

AVENO Break-In Oil SAE 30 is a mineral break-in oil for start-up filling and the breaking-in of repaired or overhauled engines. AVENO Break-In Oil SAE 30 dispenses with the use of friction coefficient improving additives (friction modifier) to considerably shorten the break-in phase for rebuilt and modified engines. The piston rings are rapidly seated. Due to its high levels of ZDDP (zinc dithiophosphate), AVENO Break-In Oil SAE 30 is particularly recommended to break-in classic V8 engines with flat tappets.

Instructions for use

AVENO Break-In Oil SAE 30 serves as a classic break-in oil and therefore can only remain in the engine for a short time (max. 1000km). The particularly high levels of anti-wear additives offer extra protection during the critical break-in phase of rebuilt engines. Please pay attention to the specifications of your engine reconditioners during the break-in phase. High engine loads and speeds are to be avoided.

Properties

- Very high levels of ZDDP
- Breaks the engine in as quickly as possible
- No friction modifier

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	92.5	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	11.1	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	105		DIN ISO 2909:2004-08
Appearance	RED		VISUELL
Density at 15°C	882	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-30	°C	ASTM D 7346:2015
Total Base Number (TBN)	4.9	mgkoh/g	ASTM D 2896:2015