## **Product Information**

## AVENO MBike 10W-40

0002-000709



## Description

AVENO MBike 10W-40 is a motor oil based on hydrocrack oils with selected additives for demanding 4-stroke motorcycles. It is characterized by a very high oxidation stability, excellent lubricating film adhesion and reliability under any load and is specially designed for wet and oil-lubricated clutches. AVENO MBike 10W-40 protects the engine from deposits and ensures a long service life.

## Instructions for use

AVENO MBike 10W-40 is suitable as motor oil for all air- and water-cooled 4-stroke motorcycles if a viscosity of 10W-40 is required. The operating instructions of the engine manufacturer must be observed!

Quality classification					
Specification					
• API SN		• JASO MA2			
Properties					
Very good shear stability		High safety reserves even under boundary lubrication conditions			
<ul> <li>Very good cold start properties</li> </ul>		<ul> <li>Optimum function of engine, clutch and transmission</li> </ul>			
Prevention of premature wear		<ul> <li>Very good resistance to oxidation and high temperature engine deposits</li> </ul>			
• Tried and tested additives					
Technical specifications					
Properties	Data	Unit	Testing under		
Kinematic Viscosity at 40°C	94.9	mm²/s	DIN 51659-2:2017-02		

rioperties	Data	onit	results under
Kinematic Viscosity at 40°C	94.9	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	14.2	mm²/s	DIN 51659-2:2017-02
Viscosity Index	154		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	852	kg/m³	DIN EN ISO 12185:1997-11
Flash Point (COC)	254	°C	DIN EN ISO 2592:2018-01
Pour Point	-39	°C	ASTM D 7346:2015

Deutsche Ölwerke Lubmin GmbH | Freesendorfer Weg 4 | 17509 Lubmin | Phone +49 38354 / 179530 | Fax +49 38354 / 179579

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.