

Product Information

AVENO FS Super 0W-30

0002-000713



Description

Aveno FS Super 0W-30 is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. Aveno FS Super 0W-30 is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

Aveno FS Super 0W-30 is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol and diesel car engines. Aveno FS Super 0W-30 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SL
- ACEA A3/B4

Approval

- Renault RN0700/RN0710

Recommendation

- BMW Longlife-01
- MB 229.5
- VOLVO VCC 95200356
- GM-LL-A-025, GM-LL-B-025
- VW 502 00/505 00

Properties

- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Suitable for catalytic converters
- Excellent cold starting properties, even at low temperatures below -30°
- A very stable and excellent viscosity behaviour and shear stability
- Excellent protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

Technical specifications

| Properties | Data | Unit | Testing under |
|------------------------------|-------------|--------------------|--------------------------|
| Kinematic Viscosity at 40°C | 60.1 | mm ² /s | DIN 51659-2:2017-02 |
| Kinematic Viscosity at 100°C | 12.0 | mm ² /s | DIN 51659-2:2017-02 |
| Viscosity Index | 200 | | DOL METHOD MA-034 |
| Appearance | YELLOWBROWN | | DOL METHOD MA-034 |
| Viscosity CCS at -35°C | 5760 | mPa*s | DOL METHOD MA-034 |
| Density at 15°C | 844 | kg/m ³ | DIN EN ISO 12185:1997-11 |
| Pour Point | -51 | °C | ASTM D 7346:2015 |
| Total Base Number (TBN) | 11.9 | mgKOH/g | ASTM D 2896:2015 |