

Product Information

AVENO WIV-Multi Supreme 5W-30

0002-000765



Description

AVENO WIV-Multi Supreme 5W-30 is a synthetic low-friction engine oil for passenger car petrol and diesel engines with and without turbocharging and direct injection. Minimization of friction, wear and fuel consumption, excellent cold start properties. Extended oil change intervals according to the manufacturer's instructions. AVENO WIV-Multi Supreme 5W-30 extends the service life of the exhaust aftertreatment system filter by reducing the concentration of ash-forming particles in the exhaust gas. Reduces the release of harmful emissions into the environment. Offers more safety thanks to the high level of protection for the motors. Thanks to its formulation with special base oils, it has a high viscosity index.

Instructions for use

AVENO WIV-Multi Supreme 5W-30 is ideal for energy-saving year-round use in modern gasoline and diesel engines. AVENO WIV-Multi Supreme 5W-30 is suitable for extended oil change intervals and extends the service life of the exhaust aftertreatment system. It meets the technical requirements of OPEL OV0401547-G30 and meets the requirements of GM dexos1 Gen2, which is a combination of parts from ILSAC GF-6, ACEA A5/B5 and GM engine tests. The AVENO WIV-Multi Supreme 5W-30 is also suitable for use in modern hybrid vehicles with petrol or diesel engines. It meets the special requirements of hybrid drive systems, including frequent start-stop cycles and low operating temperatures. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality classification

Specification

- API SP
- ACEA C3

Approval

- BMW Longlife-04
- VW 504 00/507 00
- MB-Approval 229.51
- MB-Approval 229.52

Recommendation

- GM dexos1™ Gen2
- GM dexos2™
- Opel/Vauxhall OV0401547-D30
- Opel/Vauxhall OV0401547-G30
- MB 229.31
- Porsche C30

Properties

- Fuel savings under all operating conditions
- Excellent cold start properties even at low temperatures of below -30 ° C
- Neutrality towards sealing materials
- Extremely stable and excellent viscosity behavior, shear stability
- Low evaporation tendency, thus lower oil consumption
- Safe lubricating film at high operating temperatures
- Catalyst suitability
- Excellent protection against wear, corrosion and foam formation
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	69	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	12	mm²/s	DIN 51659-2:2017-02
Viscosity Index	172		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -30°C	4750	mPa*s	ASTM D 5293:2020
Density at 15°C	848	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-33	°C	ASTM D 7346:2015
Total Base Number (TBN)	7.5	mgKOH/g	ASTM D 2896:2015