

Product Information

AVENO Low SAPS HD Ultra 5W-20

0002-000873



Description

AVENO Low SAPS HD Ultra 5W-20 is designed to provide improved fuel economy and therefore emission benefits.

Instructions for use

AVENO Low SAPS HD Ultra 5W-20 is a high-performance diesel engine oil for commercial vehicles based on synthesis technology with lowered dynamic viscosity (HTHS viscosity).

Approval

- Scania LDF-5
- MAN 3977

Properties

| Technical specifications | | | |
|------------------------------|-------|---------|--------------------------|
| Properties | Data | Unit | Testing under |
| Kinematic Viscosity at 40°C | 46.5 | mm²/s | DIN 51659-2:2017-02 |
| Kinematic Viscosity at 100°C | 8.3 | mm²/s | DIN 51659-2:2017-02 |
| Viscosity Index | 153 | | DIN ISO 2909:2004-08 |
| Appearance | BROWN | | VISUELL |
| Viscosity CCS at -30°C | 3990 | mPa*s | ASTM D 5293:2020 |
| Density at 15°C | 850 | kg/m³ | DIN EN ISO 12185:1997-11 |
| Pour Point | -45 | °C | ASTM D 7346:2015 |
| Total Base Number (TBN) | 10.1 | mgKOH/g | ASTM D 2896:2015 |