

# Product Information

## AVENO LL Motion 0809 0W-20

0002-001098



### Description

AVENO LL Motion 0809 0W-20 is a synthetic low SAPS oil for gasoline and diesel engines with and without turbocharging and with particulate filters. Thanks to its special formulation, it offers considerable fuel savings, protects the turbocharger from deposits and thus enables maximum performance. AVENO LL Motion 0809 0W-20 supports the prevention of premature fuel ignition LSPI (Low Speed Pregniton) and thus helps to prevent engine damage.

### Instructions for use

AVENO LL Motion 0809 0W-20 is a fuel-saving oil suitable for year-round use in petrol and diesel engines and is suitable for extended oil change intervals. AVENO LL Motion 0809 0W-20 is also suitable for use in modern hybrid vehicles with petrol or diesel engines. It meets the special requirements of hybrid drive systems, including frequent start-stop cycles and low operating temperatures. The operating instructions of the vehicle and engine manufacturers must be observed.

### Quality classification

#### Specification

- ACEA C5
- ACEA C6
- API SP

#### Recommendation

- Porsche C20
- VW 508 00/509 00
- Ford WSS-M2C956-A1

### Properties

- Excellent cleaning and dispersing properties
- Increased cleanliness
- Very good cold start properties
- LSPI protection against engine damage
- Excellent protection against wear, corrosion and foaming
- Protection of the turbocharger and particle filter from deposits
- Constant oil layer density at different temperature and pressure regulations
- Outstanding fuel economy in all operating conditions

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	45.1	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	8.6	mm²/s	DIN 51659-2:2017-02
Viscosity Index	171		DIN ISO 2909:2004-08
Appearance	GREEN		VISUELL
Density at 15°C	844	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-42	°C	ASTM D 7346:2015