

Product Information

AVENO Prime PS 2297 5W-30

0002-001150



Description

AVENO Prime PS 2297 5W-30 is a synthetic low-SAPS high-performance engine oil for passenger car gasoline and diesel engines. Thanks to its special additive formulation, it is particularly suitable for vehicles equipped with exhaust aftertreatment systems. AVENO Prime PS 2297 5W-30 offers excellent cold-start properties and helps to minimize fuel consumption, friction, and wear. It also supports the prevention of Low-Speed Pre-Ignition (LSPI), thereby helping to avoid potential engine damage.

Instructions for use

AVENO Prime PS 2297 5W-30 is ideally suited for fuel-efficient, year-round use in modern gasoline and diesel engines. It has been specially developed for Stellantis engines and meets their specific requirements in terms of performance and wear protection. Furthermore, AVENO Prime PS 2297 5W-30 is highly recommended for engines requiring the new Stellantis specification FPW9.55535/03. Extended oil change intervals are possible in accordance with the manufacturer's recommendations. Always observe the operating instructions of the vehicle and engine manufacturers.

Quality classification

Specification

- ACEA C2/C3
- API SP

Recommendation

- FPW9.55535/03
- GM dexos 2
- GM dexos1™ Gen3
- MB 229.31
- MB 229.51
- MB 229.52
- OV0401547-D30
- OV0401547-G30
- PSA B71 2290/2297

Properties

- Fuel savings under all operating conditions
- A secure lubricant film at high operating temperatures
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Low SAPS = reduced sulphated ash, phosphorous and sulphur
- Excellent cold starting properties, even at low temperatures below -30°C
- The function of the hydraulic valve lifter is guaranteed at all temperatures
- Extensive protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	71.9	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	11.9	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	161		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	852	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015